

UL STYLE 1332 200°C 300V TEFLON FEP WIRE  
UL STYLE 1333 150°C 300V TEFLON FEP WIRE

**TEFLON FEP WIRE UL STYLE 1332  
UL STYLE 1333**

Voltage Rating: 300 Volts

Temperature Rating: UL 1332 200°C

UL 1333 150°C

Conductor: Solid or stranding silver or nickel plated copper wire for UL 1332.

Solid or stranding tinned copper wire for UL 1333 use only.

UL 1332 may be used with tin plated copper conductors only where the individual strand diameter is 0.38mm or larger.

Insulation: Extruded FEP with 0.38 mm nominal wall thickness.

Spark Test: 4KV

Heat Shock: 250°C for 1 hour

AWG SIZE	No/dia mm	approx. O.D. mm	approx. Wt. kg/km	Standard Length m
26	1/0.404	1.17	3.31	300,500
26	7/0.160	1.24	3.89	300,500
24	1/0.511	1.27	4.28	300,500
24	7/0.203	1.37	5.16	300,500
24	19/0.127	1.40	5.23	300,500
22	1/0.643	1.41	5.71	300,500
22	7/0.254	1.52	6.93	300,500
22	19/0.160	1.56	7.08	300,500
20	1/0.813	1.58	7.90	300,500
20	7/0.320	1.72	9.70	300,500
20	19/0.203	1.78	9.99	300,500
18	1/1.024	1.78	11.10	150,300
18	7/0.404	1.97	13.96	150,300
18	19/0.254	2.03	14.16	150,300
18	34/0.18	1.96	13.20	150,300
16	1/1.29	2.05	16.00	150,300
16	19/0.287	2.20	16.30	150,300